



LCD PIN	IC PIN
C1~C64	IC3:Y1~Y64
S1~S160	IC1:Y160~Y1
S161~S320	IC2:Y160~Y1

1	2	3	4	5	6	7	8
D7	D6	D5	D4	D3	D2	D1	D0
9	10	11	12	13	14	15	16
/WR	/RD	A0	/RES	/CS	LED+	GND	VDD



- NOTE:
- 1.LCD TYPE: FSTN-NEGATIVE
 - 2.POLORIZAE MODE: TRANSMISSIVE
 - 3.VIEWING DIRECTION:6:00
 - 4.DRIVER METHOD:D:1/64DUTY,1/9BIAS,Vop=12.5V
 - 5.OPERATING TEMP.:0°C~+50°C
 - 6.STORAGE TEMP.: -20°C~+60°C
 - 7.LCD CONTROLLER:RA8835P3N,VDD=5.0V,8080 MPU
 - 8.LCD DRIVER:IST3025CA1*2(SEG),IST3025CA1(COM)
 - 9.BACKLIGHT: LED,WHITE,VF=5.0V,IF=30mA



华远显示
H-Y DISPLAY

深圳市华远显示器件有限公司
SHENZHEN HUAYUAN DISPLAY CO., LTD

DESIGN	JHG	20090330	STANDARD	REV. : A	SCALE : -
CHECKED			TECHNOLOGY	PROJECTION:	UNIT : MM
APPROVED			QA		SHEET : 1/1

DRAWING No.: HG3206401G-FT60L-VB
DRAWING TITLE: LCM

FILE NO.: 7