

1

2

3

4

5

6

160.00±0.5

152.00±0.3

140.70±0.3

122.00 V/A

115.170 A/A

11.50 MAX  
6.50±0.3  
1.204.00  
4.507.315  
4.00

4.00

4.50

4.00

4.50

4.00

4.50

4.00

4.50

4.00

4.50

4.00

4.50

4.00

4.50

4.00

4.50

4.00

4.50

4.00

4.50

4.00

4.50

4.00

4.50

4.00

4.50

4.00

4.50

4.00

4.50

4.00

4.50

4.00

4.50

4.00

4.50

4.00


4.50

# 320X240 DOTS

FRONT

REAR

REAR



NOTE:

- DISPLAY TYPE : FSTN-TRANSFLECTIVE/POSITIVE/ANTI-UV
- VIEWING DIRECTION : 6: 00
- OPERATING VOLT. : VOP=24.0V
- OPERATING TEMP. : -20°C~+70°C
- STORAGE TEMP. : -30°C~+80°C
- DRIVE METHOD : 1/240DUTY, 1/16BIAS, VDD=5.0V
- BACKLIGHT : LED(white) ILED<135mA Vf:3.1V
- CONTROLLER : RA8835AP3N
- ROHS COMPLIANT

深圳市华远显示器件有限公司  
SHENZHEN HUAYUAN DISPLAY CO., LTD

DRAWING No. : HYG32024027T-FF62L-VB  
DRAWING TITLE: LCM DRAWING  
FILE NO.: 7

F

E

D

C

B

A

J1,J2:

PIN

SYMBOL

1

VSS

2

VDD

3

V0

4

/WR

5

/RD

6

/CS

7

A0

8

/RST

9

DB0

10

DB1

11

DB2

12

DB3

13

DB4

14

DB5

15

DB6

16

DB7

17

LEDA

18

VOUT

19

LEDA

20

LEDK

E	1. DISPLAY TYPE : FSTN-TRANSFLECTIVE/POSITIVE/ANTI-UV
F	2. VIEWING DIRECTION : 6: 00
G	3. OPERATING VOLT. : VOP=24.0V
H	4. OPERATING TEMP. : -20°C~+70°C
I	5. STORAGE TEMP. : -30°C~+80°C
J	6. DRIVE METHOD : 1/240DUTY, 1/16BIAS, VDD=5.0V
K	7. BACKLIGHT : LED(white) ILED<135mA Vf:3.1V
L	8. CONTROLLER : RA8835AP3N
M	9. ROHS COMPLIANT

1

2

3

4

5

6

7

8