

REV.	CHANGE CONTENT	BY	DATE

No	Name	No	Name
1	C86	12	D5
2	/RST	13	D6
3	/RD	14	D7
4	/WR	15	VDD
5	A0	16	V0
6	/CS	17	VOUT
7	D0	18	VSS
8	D1	19	K(0V)
9	D2	20	A(5V)
10	D3	21	E-BL
11	D4		

320*240 Dots

NOTE:
1. DISPLAY TYPE: STN-NEGATIVE-TRANSMISSIVE-BLUE
2. VIEWING DIR.: 6:00
3. DRIVE METHOD: 1/240DUTY, 1/17BIAS, Vop=21.5V
4. OP. TEMP.: -20°C~+70°C
5. ST. TEMP.: -30°C~+80°C
6. LCD CONTROLLER: RA8835AP3N
7. BACKLIGHT : WHITE ,VF=5.0V, If =60mA
8. POWER SUPPLY FOR LOGIC: VDD=5.0V

深圳市华远显示器件有限公司
SHENZHEN HUAYUAN DISPLAY CO., LTD

DESIGN JHG 20080802 STANDARD
CHECKED TECHNOLOGY
APPROVED QA

DRAWING No.: HG32024010G-BT62L-VB
DRAWING TITLE: LCM DRAWING
FILE NO.: 8

REV.: B
PROJECTION:
SCALE: -
UNIT: mm
SHEET: 1/1

REV.	CHANGE CONTENT	BY	DATE

No	Name	No	Name
1	C86	12	D5
2	/RST	13	D6
3	/RD	14	D7
4	/WR	15	VDD
5	A0	16	V0
6	/CS	17	VOUT
7	D0	18	VSS
8	D1	19	K(0V)
9	D2	20	A(5V)
10	D3	21	E-BL
11	D4		

320*240 Dots

NOTE:
1. DISPLAY TYPE: STN-NEGATIVE-TRANSMISSIVE-BLUE
2. VIEWING DIR.: 6:00
3. DRIVE METHOD: 1/240DUTY, 1/17BIAS, Vop=21.5V
4. OP. TEMP.: -20°C~+70°C
5. ST. TEMP.: -30°C~+80°C
6. LCD CONTROLLER: RA8835AP3N
7. BACKLIGHT : WHITE ,VF=5.0V, If =60mA
8. POWER SUPPLY FOR LOGIC: VDD=5.0V

深圳市华远显示器件有限公司
SHENZHEN HUAYUAN DISPLAY CO., LTD

DESIGN JHG 20080802 STANDARD
CHECKED TECHNOLOGY
APPROVED QA

DRAWING No.: HG32024010G-BT62L-VB
DRAWING TITLE: LCM DRAWING
FILE NO.: 8

REV.: B
PROJECTION:
SCALE: -
UNIT: mm
SHEET: 1/1

